



4-137-0207

Vibration Transducer



Applications

- Aircraft Engines
- Industrial Turbines
- Test Cells

Features

- Ceramic bearings provide exceptional service life
- Self-generated, high level, low impedance output
- Operates to +700°F (+371°C)

Velocity Sensors

Description

CEC's 4-137 Vibration Transducers offer a technology breakthrough in velocity output vibration transducer design. These transducers use a special advanced technology bearing system that extends their service life. Yet, this design preserves the simplicity and reliability that is typical of CEC's self-generating, low impedance vibration transducers.

We designed the 4-137 Vibration Transducers for turbine applications. Use them in hot sections where high temperatures cause problems with other instruments. They simplify your system because low impedance, high level output does not require special amplifiers or low-noise cables. They have low sensitivity to transverse accelerations, and you can mount them in any plane. Their rugged construction and new bearing system insure high reliability

and long service life.

CEC 4-137 Vibration Transducers use a seismic mass magnet that moves on special ceramic bearings. A coil is attached to the case, and movement between the magnet and coil produces the output signal when the case vibrates. This air damped system operates above its natural frequency. The mV output is proportional to velocity.

Model 4-137-0207 is designed as a replacement for the 4-125-L207.



4-137-0207 Vibration Transducer

Performance Specifications

Sensitivity:	70.72 mV/ips $\pm 2\%$ into 100k Ω load. Measured at +77°F (+25°C) in the vertical position, with a sinusoidal driving force applied perpendicular to the base at 100 Hz, 1 in/sec peak (25.4 mm/sec).
Dynamic Range	
Frequency:	45 Hz to 1500 Hz
Amplitude:	0.07 inch peak-to-peak max
Acceleration:	1.0 g to 50 g peak vertical 1.5 g to 50 g horizontal
Acceleration Threshold:	0.3 g peak vertical 1.0 g peak horizontal
Frequency Response:	$\pm 6\%$ through frequency range referenced to 100 Hz at +77°F (+25°C) and 1 in/sec peak (25 mm/sec)
Linearity:	$\pm 5\%$, 1 g to 20 g's peak @100 Hz
Temperature Range	-65°F to +700°F (-54°C to +371°C)
Thermal Coefficient of Sensitivity:	$\pm 0.02\%/^{\circ}\text{F}$ from reference +77°F ($\pm 0.036\%/^{\circ}\text{C}$ from reference +25°C)
Damped Resonant Frequency:	20 Hz
Excitation:	Self-generating
Coil Resistance:	460 $\Omega \pm 25\%$
Insulation Resistance:	0.1 megaohm minimum at +700°F (+371°C)
Polarity:	Pin 2 is positive when case is moved upward
Shock:	50g max in any direction
Sealing:	Hermetically sealed, all welded construction
Weight	3.5 oz. (99.2 g) maximum

Hazardous Approvals



North America
 CSA C/US Class I, Division I, Groups A, B, C and D
 Class I, Division 2, Groups A, B, C and D



European
 ATEX EEx ia IIB or IIC T6 - T1
 EEx nA II T6 - T1 X

Optional Accessories

- P/N 169500-XXXX, High temperature cable and connector assembly (-XXXX = length in inches; e.g.: 60-inch cable is P/N 169500-0060)
- High temperature connector P/N 173960

Ordering Information

When ordering, specify the full part number 4-137-0207. Other configurations and sensitivities are available. Please contact CEC for details. Order mating connectors and cable assemblies separately. In keeping with CEC's policy of continuing product improvement, specifications may be changed without notice.

